

INSTALLATION INSTRUCTIONS FOR  
**WALL MOUNT NATURAL GAS**  
OUTDOOR INSTALLATION

This lantern must be installed by a certified plumber to conform to local codes or in absence of local codes with the national fuel gas code ANSI Z223.1.

**FOR YOUR SAFETY**

**If you smell gas:**

- 1. Shut off gas to the appliance.**
- 2. Extinguish any open flame.**
- 3. If odor continues, immediately call your gas supplier.**

**FOR YOUR SAFETY**

**DO NOT store or use gasoline or any other flammable vapors and liquids in the vicinity of this, or any other appliance.**

*ATTENTION INSTALLER: Leave these instructions with the appliance so the consumer will retain them for future reference.*

**INSTALLATION INSTRUCTIONS**

*NOTE: The minimum clearance from combustible constructions is 12" top by 6" side (excluding ornamentation).*

- 1) Adjust natural gas inlet pressure to 7.0 inches WC.
- 2) Install brass mounting bracket. If mounting on brick or masonry, anchors will need to be used (not supplied).
- 3) Reduce gas supply line from exterior wall to 1/4" aluminum tubing using approved fittings only.
- 4) Make a aluminum coil using 1/4" OD aluminum tubing to allow hook-up of gas supply line to 1/4" flare male connector located in wall mounting box of lantern. All hook-ups must be made with in the depth and height of the lantern mounting box.
- 5) Attach fixture to brass mounting bracket.